		Page : 1
	SAFETY DATA SHEET	Revised edition no : 0
		Date : 6 / 12 / 2016
BUZWAIK		Supersedes : 0 / 0 / 0
Nitrogen (refrigerated)		SDS_LIN
	2.2 : Non-flammable, non- toxic gases	
Warning ECTION 1. Identification of t	the substance/mixture and of the company/undertak	kina
.1. Product identifier		
Trade name SDS Nr	: Nitrogen (refrigerated) : SDS_LIN	
Chemical description	: Nitrogen (refrigerated)	
	CAS No :7727-37-9 EC No :231-783-9 Index No :	
Registration-No.	: Listed in Annex IV / V REACH, exempted from registrat	tion.
Chemical formula	: N2	
.2. Relevant identified uses	of the substance or mixture and uses advised again	<u>nst</u>
Relevant identified uses	 Industrial and professional. Perform risk assessment pr Use for manufacture of electronic/photovoltaic component Test gas/Calibration gas. Purging. Laboratory use. Shield gas for welding processes. Contact supplier for more information on uses. 	
.3. Details of the supplier of	f the safety data sheet	
Company identification	: BUZWAIR INDUSTRIAL GASES FACTORIES PO Box 319 Doha Qatar	
.4. Emergency telephone nu	umber	
Emergency telephone number	er : +974 4451 6976	
ECTION 2. Hazards identific	ation	
.1. Classification of the sub	stance or mixture	
	de Regulation EC 1272/2008 (CLP)	
 Physical hazards 	: Gases under pressure - Refrigerated liquefied gas - Wa	arning - (CLP : Press. Gas) - H281
Classification EC 67/548 or EC	<u>1999/45</u>	
	 Not classified as dangerous substance / mixture. Not included in Annex VI. No EC labelling required. 	
.2. Label elements		
Labelling Regulation EC 1272/2	<u>008 (CLP)</u>	
Hazard pictograms	$\langle \cdot \rangle$	
	\mathbf{v}	
	S FACTORIES In cas	se of emergency : +974 4451 6



Page : 2

Revised edition no : 0 Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 2. Hazards identification (continued)

 Hazard pictograms code 	: GHS04	
 Signal word 	: Warning	
 Hazard statements 	: H281 - Contains refrigerated gas; may cause cryogenic burns or injury.	
 Precautionary statements 		
- Prevention	: P282 - Wear cold insulating gloves/face shield/eye protection.	
- Response	: P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice / attention.	
- Storage	: P403 - Store in a well-ventilated place.	
2.3. Other hazards		
	: Asphyxiant in high concentrations.	

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.	
oubolunioc.	

Substance name		Contents	CAS No EC No Index No Registration no	Classification(DSD)	Classification(CLP)
Nitrogen (refrigerated)	:	100 %	7727-37-9 231-783-9	Not classified (DSD)	Press. Gas Refrigerated (H281)
			* 1		

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

SECTION 4. First aid measures

<u>4.2</u>.

4.1. Description of first aid measures

- Inhalation	 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. 	
- Skin contact	: In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.	
- Eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes.	
- Ingestion	: Ingestion is not considered a potential route of exposure.	
2. Most important symptoms and effects, both acute and delayed		

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

4.3. Indication of any immediate medical attention and special treatment needed

: None.



Page : 3 Revised edition no : 0

Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 5. Firefighting measures

5.1. Extinguishing media	
- Suitable extinguishing media - Unsuitable extinguishing media	:Water spray or fog. :Do not use water jet to extinguish.
5.2. Special hazards arising from th	e substance or mixture
Specific hazards Hazardous combustion products	: Exposure to fire may cause containers to rupture/explode. : None.
5.3. Advice for fire-fighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases fro If possible, stop flow of product. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire. Use water spray or fog to knock down fire fumes if possible.
Special protective equipment for fire fighters	 Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	 Try to stop release. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Evacuate area. Use protective clothing. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. 		
6.2. Environmental precautions			
	: Try to stop release.		
6.3. Methods and material for containment and cleaning up			
	: Liquid spillages can cause embrittlement of structural materials. Ventilate area.		
6.4. Reference to other sections	: See also sections 8 and 13.		

SECTION 7. Handling and storage

7.1. Precautions for safe handling

 Safe use of the product
 : Only experienced and properly instructed persons should handle gases under pressure. The substance must be handled in accordance with good industrial hygiene and safety procedures. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not smoke while handling product. Ensure the complete gas system was (or is regularily) checked for leaks before use. Consider pressure relief device(s) in gas installations.



Page : 4 Revised edition no : 0

Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

: None.

SDS_LIN

SECTION 7. Handling and storage (continued)

Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container.
7.2. Conditions for safe storage, inc	luding any incompatibilities
	 Observe all regulations and local requirements regarding storage of containers. Keep container below 50°C in a well ventilated place. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Containers should not be stored in conditions likely to encourage corrosion. Keep away from combustible materials.
7.3. Specific end use(s)	

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

8.1. Control parameters	
DNEL: Derived no effect level(Workers)	
	: No data available.
PNEC: Predicted no effect concentration	
	: No data available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	 Systems under pressure shoud be regularily checked for leakages. Oxygen detectors should be used when asphixiating gases may be released. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g. personal protective equipment	 PPE compliant to the recommended EN/ISO standards should be selected. A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: Protect eyes, face and skin from liquid splashes.
Eye/face protection	: Wear goggles and a face shield when transfilling or breaking transfer connections. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
 Respiratory protection 	: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: Standard EN 511 - Cold insulating gloves. Wear cold insulating gloves when transfilling or breaking transfer connections.



Page : 5 Revised edition no : 0

Revised edition no : 0 Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 8. Exposure controls/personal protection (continued)

8.2.3. Environmental exposure controls

: None necessary.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Colourless liquid.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
pH value	: Not applicable.
Molar mass [g/mol]	: 28
Melting point [°C]	: -210
Boiling point [°C]	: -196
Critical temperature [°C]	: -147
Flash point [°C]	: Not applicable for gases and gas-mixtures.
Evaporation rate (ether=1)	: Not applicable for gases and gas-mixtures.
Flammability range [vol% in air]	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Relative density, gas (air=1)	: 0.97
Relative density, liquid (water=1)	: 0.8
Solubility in water [mg/l]	: 20
Partition coefficient n-octanol/water [log Kow]	: Not applicable for inorganic gases.
Auto-ignition temperature [°C]	: Not applicable.
Viscosity at 20°C [mPa.s]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: None.
9.2. Other information	
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10. Stability and reactivity

10.1. Reactivity		
	: No reactivity hazard other than the effects described in sub-sections below.	
10.2. Chemical stability		
	: Stable under normal conditions.	
10.3. Possibility of hazardous react	tions	
	: None.	
10.4. Conditions to avoid		
	: None under recommended storage and handling conditions (see section 7).	
10.5. Incompatible materials		
	: None. For additional information on compatibility refer to ISO 11114.	
10.6. Hazardous decomposition products		



Page : 6 Revised edition no : 0

Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 10. Stability and reactivity (continued)

: None.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

12.1. Toxicity

	: No ecological damage caused by this product.	
12.2. Persistence and degradabilit	Y	
	: No ecological damage caused by this product.	
12.3. Bioaccumulative potential		
	: No ecological damage caused by this product.	
12.4. Mobility in soil		
	: No ecological damage caused by this product.	
12.5. Results of PBT and vPvB assessment		
	: Not classified as PBT or vPvB.	
12.6. Other adverse effects		
	: Can cause frost damage to vegetation.	
Effect on ozone layer	: None.	
Effect on the global warming	: No known effects from this product.	

SECTION 13. Disposal considerations

13.1. Waste treatment methods

	: May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www. eiga.org for more guidance on suitable disposal methods. Consult supplier for specific recommendations.
List of hazardous wastes	: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	: None.



Page : 7

Revised edition no : 0 Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 14. Transport information

UN number Labelling ADR, IMDG, IATA	: 1977
	: 2.2 : Non-flammable, non-toxic gases
Land transport (ADR/RID)	
H.I. pr	: 22
UN proper shipping name	: NITROGEN, REFRIGERATED LIQUID
Transport hazard class(es)	: 2
Classification code	: 3 A
Packing Instruction(s)	: P203
Tunnel Restriction	: C/E Tank carriage: Passage forbidden through tunnels of category C, D andE;Other carriage: Passage forbidden through tunnels of category E
Environmental hazards	: None.
<u>Sea transport (IMDG)</u>	
Proper shipping name	: NITROGEN, REFRIGERATED LIQUID
Class	: 2.2
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
Packing instruction	: P203
IMDG-Marine pollutant	: No
Air transport (ICAO-TI / IATA-DGR)	
Proper shipping name (IATA)	: NITROGEN, REFRIGERATED LIQUID
Class	: 2.2
Passenger and Cargo Aircraft	: Allowed.
Packing instruction - Passenger and Cargo Aircraft	: 202
Cargo Aircraft only	: Allowed.
Packing instruction - Cargo Aircraft only	: 202
Special precautions for user	
	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure there is adequate ventilation.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: Not applicable.



Page : 8 Revised edition no : 0

Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Nitrogen (refrigerated)

SDS_LIN

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** legislation **Restrictions on use** : None. Seveso directive 96/82/EC : Not covered. National legislation National legislation : Ensure all national/local regulations are observed. 15.2. Chemical safety assessment : A CSA does not need to be carried out for this product. **SECTION 16.** Other information Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010. **Training advice** : The hazard of asphyxiation is often overlooked and must be stressed during operator training. List of full text of H-statements in : H281 - Contains refrigerated gas; may cause cryogenic burns or injury. section 3. **Further information** : This Safety Data Sheet has been established in accordance with the applicable European Union legislation. **DISCLAIMER OF LIABILITY** Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document